



East Timor Roofing & Training Unipessoal Lda

Sales /Manufacturing

Rua Vila Nova,

Villa Nova Baucau

Ph/Fax: 4130027

Web: www.easttimorroofing.com

Email: etroofing.tl@gmail.com




Established by The Rotary Clubs
of Doncaster, Melbourne and Lilydale, Australia
for the benefit of the people of Timor-Leste

Suppliers of quality steel roofing, framing, water storage tanks and grain silos to your custom equirements.

Manufactured in Timor Leste from ONLY quality Australian Bluescope steel.

METAL ROOF TRUSSES



Prefabricated metal roof trusses up to 12.0m with varying roof pitches can be manufactured.

AQUAPLATE WATER TANKS



500 to 16000 litre capacity corrugated water tanks. Manufactured from quality Bluescope Aquaplate®.

CORRUGATED /RIBBED ROOFING AND WALLING




Corrugated and Ribbed Roofing 0.42mm x 760mm cover width roofing in Zinalume® and Colorbond® to your custom length. *Colorbond colours: Headland Red, Surfmist and Pale Eucalypt.*

CORRUGATED GRAIN SILOS



200 and 400 litre capacity corrugated grain silos. Fitted with an air tight 100mm PVC screw cap. Other larger airtight silos for bulk storage are also available.

RIDGE , BARGE CAPPING AND FLASHING



Ridge and barge cap and valley gutter standard 400mm wide flashing or folded to your requirements. *Maximum length 6.0m.*

METAL TOOL BOXES



Gavanized Tool Boxes in either standard or custom sizes.

GUTTERING



0.55mm Zinalume® Gutter to your custom length. Brackets to suit

CEILING BATTEN – TOP HAT



40mm x 0.75mm Top Hat Batten. *Length 6.0m.*

METAL FRAMING - GALVASPAN® and TRUECORE®



Galvaspan Purlins, Girts and Truecore lightweight steel framing. Available in a range of thicknesses and sizes to suit your specifications.


GALVANISED BRACKETS, FITTINGS AND FIXTURES



All of the brackets, screws and fixtures necessary to fix roofing iron are held in stock. Also 1.2 and 1.5mm thickness galvanized brackets and fittings made to your requirements.

Metal Roof Trusses

Our trusses are designed by qualified engineers to Australian Standards, normally using a design wind speed of 38 m/sec with a uniform live load of 0.25 kPa.



They utilise Galvaspan sections with extra material at the most stressed areas to provide trusses which perform well.

Corrugated and Ribbed Roofing

Corrugated and ribbed sheeting is rolled from quality Australian steel in our factory to your custom length. This avoids sheet joints and results in a superior job. Stock lengths also available. The Zinalume and Colorbond is 0.42 mm thickness, total sheet width of 840 mm with a cover width of 762 mm. Weight is 4.3 kg/m.



We always have ample stocks of Zinalume available for immediate delivery. Colorbond colours stocked are Headland Red, Surfmist and Pale Eucalypt.

Ridge, Barge Capping & Flashing

Ridge, Barge capping and Flashing – Ridge and barge capping, valley gutters and flashing are made from 0.55 mm G300 material and not from higher tensile material which has a tendency to crack.



Available in Zinalume and Colorbond Headland Red G300 only.

Flashings can be obtained in widths from 100 mm to 1200 mm.

Guttering

Gutter is 125mm Ogee profile. Made from 0.55mm Zinalume and rolled to any length to suit requirements.



We can fit stop ends, outlets and corners if required.

A supply of water is often a problem so why not collect water from your roof into guttering run to a tank.

Metal Purlins and Framing

Purlins are rolled in Galvaspan 150 mm x 40 mm x 1.2mm and 100 mm x 40 mm x 1.2 mm C and U sections. These sections are also used to construct trusses. Other lighter and thus more economical sections are also rolled from Truecore in 100 mm, 90 mm and 75 mm deep profiles, with metal thicknesses of 1.00 mm, 0.75 mm and 0.55 mm.



This material is particularly popular for making stable and accurate wall frame stud and track.

Building strap is 30x1.2 and 50x1.5 high tensile Gal. Lengths to suit requirements.

Aquaplate Water Tanks

Aquaplate is a laminated steel product with exceptional durability designed to meet the stringent quality requirements for the storage of drinking water.



The substrate conforms to AS1397 with food grade polymer film to AS/NZS 4020 200µm thick laminated to the steel.

Tank bases are constructed from Aquaplate with film on both sides for maximum product life.

Standard Sizes

Capacity (l)	Diameter (m)	Height (m)
500	0.9	0.80
1000	1.30	0.80
2000	1.30	1.60
3000	1.55	1.60
5500	2.10	1.60
7000	2.35	1.60
10000	2.35	2.35
16000	3.00	2.35

Other sizes available on request

Metal Tool Boxes

Metal tool boxes can be made in sizes to suit requirements with maximum length 1.1m.



Made from 0.55mm Galvanized sheet & Zinc coated fittings which include sturdy carry handles and a hasp and staple for locking. Larger sizes fitted with reinforced lid and chain lid restraints.

Corrugated Grain Silos

Silos are airtight to prevent loss to weevils, rats and mice and to ensure seed remains viable.



Airtight grain silos made from 0.6mm thickness corrugated Galvanized sheet with external Aquaplate bottom for added protection. Silos are fitted with airtight 100mm PVC screw cap inlet/outlet at top. Or also available with separate airtight 100mm PVC screw cap inlet at top and outlet at bottom.

Standard Sizes

Capacity (l)	Diameter (m)	Height (m)
200	600	800
400	800	800
500	900	800
2000	1300	1600
3000	1550	1600

Other sizes available on request

Roof, Ceiling & Wall Battens

40mm x 40mm x 0.75mm Truecore in 6.0m stock lengths.



Galvanised Brackets & Fittings

ETR Universal Purlin brackets made from 1.2 thickness hi tensile Galvanized steel, can be folded to suit left or right hand application.



Can be used as a purlin bracket or for many other applications where a hold down bracket is required.

Also, brackets folded from 1.2mm or 1.5mm thickness, hi tensile Galvanized steel.



East Timor Roofing & Training Unipessoal Lda

Sales/Manufacturing

Rua Vila Nova,
Villa Nova Baucau
Ph/Fax: 4130027

Email: etroofing.tl@gmail.com

Web: www.easttimorroofing.com

Publication: ETR-01, May 2018